

ROADRUNNER™ AHD CAMERA, EXTERIOR WEDGE

ON-BOARD VIDEO SECURITY SYSTEM



FEATURES

- Full HD (1080p) Resolution
- Varifocal Lens
- Vandal and Impact Resistant
- IP67 Rated
- Optional Tempered-Glass Viewing Window

RUGGED AND RELIABLE

Providing the highest quality recording in a rugged and vandal resistant enclosure, the exterior wedge camera is designed for optimal viewing and flexibility for exterior locations.

UV COATED DOME

The exterior wedge camera features a UV coated dome for additional exterior protection.

ROADRUNNER™ AHD CAMERA, EXTERIOR WEDGE

ON-BOARD VIDEO SECURITY SYSTEM

TECHNICAL DATA

Product Ordering Information	
Part/Model Number (N. America)	RR-CW1-CS-AHD (Curbside View); RR-CW1-SS-AHD (Streetside View) Tempered Glass Options: RR-CW1-TG-CS-AHD (Curbside View); RR-CW1-TG-SS-AHD (Streetside View)
Electrical Properties	
Operating Voltage	12 VDC
Power Consumption	2.2 W
Current Consumption	180 mA
Interfaces	
12 VDC In	1, 2-pin Minifit Jr
Video Output	1, BNC Socket (Yellow)
Mechanical Properties	
Weight	0.57 kg, 1.26 lbs
Dimensions	103 mm x 92 mm x 172 mm, 4.05" x 3.62" x 6.7"
Housing Screws	Security Torx
Environment	
Operating Temperature	-10°C to 50°C, 14°F to 122°F
Relative Humidity	0% to 96% (Non-condensing)
Ingress Protection	IP67
Standards	
FCC	✓
CE	✓
Image	
Image Sensor	1/2.9" 2.1M Sony CMOS
Field of View	34° - 70° Horizontal; 26° - 51.4° Vertical
Resolution	F-HD (1920x1080), HD (1280x720), D1 (704x480), n-HD (640x360), CIF (352x240)
Frame Rate	1920x1080p @ 30 fps
Scanning System	Progressive
Shutter Speed	Automatic, 1/30, 1/60, Flicker-less Mode (FLK) ~ 1/50,000 Sec
Pan / Tilt / Zoom	Digital
Light Sensitivity Black/White; Color	0.1 Lux; 1.0 Lux
Noise Reduction	Dynamic, 3D
Signal-To-Noise-Ratio	50dB or Higher
Image Settings	Color, Brightness, Sharpness, Auto Gamma Control, Defog, White Balance
Video	
Video Output Signal	AHD, CVBS
Mechanics	
Lens	Varifocal 2.8 mm - 12 mm

Features and specifications are subject to change without notice. May 2020.

www.luminator.com